


# AMIGO 36 S/EW

Part number 3108209



## Description

Ultra-flat LED luminaire, includes:

- Galvanized perforated sheet, powder-coated housing
- Optics made up of PMMA optics and white polycarbonate reflectors to optimise light distribution
- UGR<16
- Remote ON/OFF driver included

Options:

- Dimmable DALI options available. Consult factory
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

**Product data**

ETIM Group:	EG000027	ETIM Class:	EC001744
-------------	----------	-------------	----------

**General information**

Lampholder:	LED	Light source:	LED
Lightsource lumen output [lm]:	5110	Luminaire lumen output [lm]:	3604
Luminaire wattage [W]:	25 W	Luminous efficacy [lm/W]:	144
CRI:	80	Kelvin:	4000
Colour / Finish:	WH-87 / White / Textured	IP degree of protection:	IP20
IK-J-xxIP:	IK05 0.70J xx3	Insulation class:	II
Optic:	SYMMETRIC EXTRA-WIDE	Net weight [kg]:	3.662

**Mechanical features**

Shape:	SQUARE > 300 MM	Housing material:	PAINTED STEEL
Glow wire test [°C]:	650 °C		

**Electrical features**

Voltage type:	AC	Power factor / COS Φ:	>0.9
Inrush current [A/μs]:	8 / 40		

**Installation**

Application area:	Indoor	Mounting type:	Ceiling recessed
Min. ambient temperature [°C]:	-20	Max. ambient temperature [°C]:	45

**Light features**

MacAdam:	3	Lumen maintenance:	L80B10@84000h
Distribution of light emission:	Direct	UGR max.:	15.5

## Photometric data

---

Photometric Lvk AMIGO 36 S/EW 1


## Optional accessories

---


AMIGO 36



**3109055**  
Driver DALI



**19-02531**  
Ceiling kit



**3111872**  
Kit EM3P

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at [www.performanceinlighting.com/qr/qr/company/terms-and-conditions](http://www.performanceinlighting.com/qr/qr/company/terms-and-conditions)