


Baleva

451203.002.1 | Linear luminaires

Ceiling and wall luminaires
 4051859180630
 LED
 L 1200, B 46, H 60



Linear luminaire with timeless functional design. Ideal for sanitary areas, corridors, waiting areas, nursing homes, patient rooms. Body and end caps made of white plastic. Diffuser: plastic (polycarbonate), opal, shockproof. Homogeneous and smooth light distribution. Diffuser can be assembled without the use of tools. Quick and easy to install. Can be installed horizontally and vertically. 2 central cable inlets for looping the cable. Converter integrated and encapsulated.

Colour

Colour white

Dimensions

Length L 1.200 mm
 Width B 46 mm
 Height H 60 mm
 Weight 875 g

Lamp

Lamp LED
 Colour temperature 4000K
 Colour rendering index (CRI) 80
 Lifetime 50000 h (L80/B10)

Lighting technology

Beam Angle 150°/107°
 Photobiological safety according to EN 62471 Risk group 0

Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	10
Luminaires on B16A fuse	16
Luminaires on C10A fuse	20
Luminaires on C16A fuse	32
Inrush current / inrush current duration	5 A
Colour temperature 1	4.000 K
System power 1	19 W
Rated luminous flux 1	2.050 lm
Glare evaluation UGR (4H 8H) 1	23,7
Luminaire efficacy 1	108 lm/W

Approbations

Type of Protection	IP 40, IP 44
Anmerkung Schutzart	IP 40 Ceiling mounting, IP 44 wall mounting
Protection Class	II
Glow Wire Test	650°C - 30 seconds
Impact Protection	IK07 (2 Joule)
Other Marks	WEEE mark
Ambient temperature min.	-30 °C
Ambient temperature max.	40 °C
ULOR	18,1 %
CIE Flux Code / CEN Flux Code	39 68 88 82 100
Energy efficiency class LED	A+
Energy class of included lamp	A+