

PRODUCT PHOTOGRAPH



TECHNICAL DRAWING

COMPATIBLE WITH

— On/Off Driver: N/A

— Triac Driver: N/A

— Dali Driver: N/A

GENERAL INFORMATION

Product Code	8254401
Product Category	Linear
Product Family	Linear Lighting Profiles
Mounting Location	Ceiling
Application Environment	Indoor

DIMENSION & WEIGHT

LxWxH (cm)	L: 120 W: 3,8 H: 7
Cut out (cm)	0
Weight (Kgr)	2.86

MATERIAL & COLOR

Product Color	White
Body Material	Aluminium
Cover Material	PMMA

APPLICATION & MOUNTING

Ambient Working Temp.	45 C
Type of Protection	IP20
Protection Class IK	IK04
Dimmable	NO
Type of Dimming (Optional)	N/A
Mounting type	Surface
Mounting Depth (cm)	Ceiling
Led Module Replaceable	N/A
Light Source	N/A
Adjustable	No



NOVA LUCE

PRODUCT DATASHEET

Version: 001

ELECTRICAL DATA

Power (Nominal)	40 W
Input voltage (Nominal)	220-240Vac
Mains Frequency	50/60Hz
Output voltage	N/A
Output Current	N/A
Power Factor	N/A
Efficiency	N/A
SVM	N/A
Pst	N/A
Class	I

PHOTOMETRICAL DATA

Luminous Flux	2613 lm
Luminous Efficacy	65,33 lm/W
Color Temperature	4000 K
Light Color (Designation)	Neutral White
CRI	>80
SDCM	<6
Beam Angle	120
UGR	N/A

LIFESPAN

Lifetime	50000 hours
----------	--------------------

CERTIFICATES

Certificates	CE, UKCA
--------------	-----------------

WARRANTY

Warranty	5 years
----------	----------------

LIGHT DISTRIBUTION

NOVA LUCE S.A

Schimatari Viotias
32009, Greece

+30 22620 58 121
+30 22620 56 743

info@novaluce.com
www.novaluce.com

