


Date
Customer
Project
Type

Medard Track 48V Adjustable 42 1x LED 3000K Medium DALI DI White Structure




The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.



Specifications

Material	13430509
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G7
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
Binning (SDCM)	2
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	23.9
Input Voltage	48Vdc
Luminaire power (W)	10.5
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI
DALI Standard	DALI version-1
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	H 360° V 360°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	320.0
Delivered lumens (lm)	702
Efficacy (lm/W)	66
Glare rating	13
Remark	<ul style="list-style-type: none"> • 3500K and 4000K on request • This white Track 48V luminaire comes with a white track adapter. Exceptions are only possible on request. • This is not a complete product. Pista track 48V system required.

TM30 & CRI diagram



Light distribution & beam diagram

