

**XFIVE RECESSED|SURFACE****FVRS01FC MBK**

Application field / Finishing	<b>Indoor / Black</b>
Protection class	<b>Classe III</b>
IP / IK rating	<b>IP40</b>
Input voltage	<b>48V DC</b>
Ambient temperature	<b>-20 ÷ +45 °C</b>
Warranty	<b>5 years</b>
Weight	<b>0,03 kg</b>

**Description / Descriere / Descrizione**

EN - Electrical, linear, flexible connector of black polycarbonate, for two recessed or surface XFIVE profiles.

RO - Element de conexiune electrică, liniară, flexibil, din polycarbonat negru, pentru două profile încastrate sau aparente XFIVE.

IT - Connettore elettrico lineare, flessibile, in polycarbonato nero, per due profili XFIVE da incasso o da superficie XFIVE.

**Electric gear / Aparataj de alimentare / Alimentazione**

EN - Electrical circuit for 48V DC with two electrical contacts for the track.

RO - Circuit electric de 48V DC cu două contacte electrice pentru profil.

IT - Circuito elettrico per 48V DC con due contatti elettrici per profilo.

**Standards**

EN 60598-1:2021, EN 60598-2-1:2021, EN 60529:1992 + A2:2013, EN 55015:2019 + A11:2020, EN 61000-3-2:2019, EN 61000-3-3:2013 + A1:2019, EN 61547:2023, EN 62717:2017+A2:2019, EN 62722-2-1:2023.

