

# Datasheet

PROLED ARMADILLO CV

**PROLED**<sup>®</sup>

Article number: L5252402  
Article name: PROLED ARMADILLO CV  
Article description: PROLED SWITCHING POWER SUPPLY ARMADILLO CV 24-020  
GTIN: 4251158408699



picture similar

## Electrical properties:

Input:	
Voltage supply:	220 - 240 VAC ; 50 - 60 Hz ; 0.21 A
Inrush current:	< 10 A ; < 300 $\mu$ s
Efficacy:	82 %
Power factor:	0,55
Output:	
Output:	24 VDC; 0.83 A; 20 W
Output adjustable:	—

## Technical properties:

Primary connection:	Screw terminal; 0.75 - 1.5 mm <sup>2</sup>
Secondary connection:	Screw terminal; 0.5 - 1.5 mm <sup>2</sup>
Control:	no
PWM dimmer:	—
Fan:	without fan

Date: 7.5.2024

Technical amendments and errors reserved.

**PROLED**<sup>®</sup>

MBN GmbH | Balthasar-Schaller-Str. 3 | 86616 Friedberg | Germany

Phone +49.821.60099-0 | Fax +49.821.60099-99

Central: info@proled.com | Internet: www.proled.com

Registered office of the company: Friedberg | Amtsgericht Augsburg HRB 19419 | Managing Director: Dr. Bernhard Steidl, Christian von Sassen

**Protection properties:**

Protections:	Short cut, Over power, Over temperature, Open circuit
Electrical safety class:	II
IP classification:	IP20
MM sign:	✓

**Connection to Fuses:**

Fuse type:	B10	B13	B16	B20	B25	C10	C13	C16	C20	C25	D10	D13	D16	D20
Number units:	17	23	28	35	44	37	48	59	74	92	74	96	118	148

**Housing and size:**

Size:	154 x 50 x 14 mm (l x w x h)
Housing colour:	white
Housing material:	Plastics
Product weight:	0,100 kg

**Mounting instructions:**

For outdoor use:	–
Mounting place:	Stand mounting, Wall-ceiling mounting
Mounting type:	screwable
Ambient temperature:	-20 °C to 45 °C
Max. case temperature:	85 °C

**Flags:**

