

# Datasheet

PROLED TURTLE CCU IP 65 ROUND

# PROLED®

Article number: L5240512R  
Article name: PROLED TURTLE CCU IP 65 ROUND  
Article description: PROLED SWITCHING POWER SUPPLY TURTLE CCU IP65 ROUND 500-012  
GTIN: 4251158429052



picture similar

## Electrical properties:

Input:	
Voltage supply:	220 - 240 VAC ; 50 - 60 Hz ; 0.08 A
Inrush current:	< 5 A ; < 300 μs
Efficacy:	82 %
Power factor:	0,9
Output:	
Output:	500 mA CC; 8 - 24 VDC; 12 W
Output adjustable:	—

## Technical properties:

Primary connection:	cable to open wires; 2 x 0.75 mm <sup>2</sup>
Secondary connection:	cable to open wires; 2 x 0.82 mm <sup>2</sup>
Control:	no
PWM dimmer:	—
Fan:	without fan

Date: 30.4.2024

Technical amendments and errors reserved.

**PROLED®**

MBN GmbH | Balthasar-Schaller-Str. 3 | 86616 Friedberg | Germany

Phone +49.821.60099-0 | Fax +49.821.60099-99

Central: info@proled.com | Internet: www.proled.com

Registered office of the company: Friedberg | Amtsgericht Augsburg HRB 19419 | Managing Director: Dr. Bernhard Steidl, Christian von Sassen

**Protection properties:**

Protections:	Short cut, Over power, Over temperature, Open circuit
Electrical safety class:	II
IP classification:	IP65
MM sign:	✓

**Housing and size:**

Size:	50 x 40 x 24 mm (l x w x h)
Housing colour:	white
Housing material:	Plastics
Product weight:	0,090 kg

**Mounting instructions:**

For outdoor use:	✓
Mounting place:	Stand mounting, Wall-ceiling mounting, Wall-ceiling installation
Mounting type:	screwable
Ambient temperature:	-20 °C to 50 °C
Max. case temperature:	80 °C

**Flags:**