

# Datasheet

PROLED PROLED SWITCHING POWER SUPPLIES IP67

# PROLED®

Article number: L5202424W  
Article name: PROLED PROLED SWITCHING POWER SUPPLIES IP67  
Article description: PROLED SWITCHING POWER SUPPLY IP67 24-240  
GTIN: 4251158443584



picture similar

## Electrical properties:

Input:	
Voltage supply:	100 - 240 VAC ; 50 - 60 Hz ; 2.6 A
Inrush current:	< 75 A ; < 300 µs
Efficacy:	91 %
Power factor:	0,95
Output:	
Output:	24 VDC; 10 A; 240 W
Output adjustable:	—

## Technical properties:

Primary connection:	cable to open wires; 3 x 1 mm <sup>2</sup>
Secondary connection:	cable to open wires; 2 x 1.5 mm <sup>2</sup>
Control:	no
PWM dimmer:	—
Fan:	without fan

Date: 7.5.2024

Technical amendments and errors reserved.

**PROLED®**

MBN GmbH | Balthasar-Schaller-Str. 3 | 86616 Friedberg | Germany

Phone +49.821.60099-0 | Fax +49.821.60099-99

Central: info@proled.com | Internet: www.proled.com

Registered office of the company: Friedberg | Amtsgericht Augsburg HRB 19419 | Managing Director: Dr. Bernhard Steidl, Christian von Sassen

**Protection properties:**

Protections:	Short cut, Over power, Over temperature, Open circuit
Electrical safety class:	I
IP classification:	IP67
MM sign:	✓

**Connection to Fuses:**

Fuse type:	B10	B13	B16	B20	B25	C10	C13	C16	C20	C25	D10	D13	D16	D20
Number units:	2	3	3	4	5	4	6	7	9	12	9	12	15	19

**Housing and size:**

Size:	249 x 70 x 40 mm (l x w x h)
Housing colour:	grey
Housing material:	alu
Product weight:	1,300 kg

**Mounting instructions:**

For outdoor use:	✓
Mounting place:	Stand mounting, Wall-ceiling mounting
Mounting type:	screwable
Ambient temperature:	-20 °C to 50 °C
Max. case temperature:	80 °C

**Flags:**

