

**XFIVE RECESSED|SURFACE****FVRS01DV MBK**

Application field / Finishing	<b>Indoor / Mat black</b>
Mounting / Light orientation type	<b>Ceiling mounted; Ceiling recessed</b>
IP / IK rating	<b>IP40</b>
Input voltage	<b>220-240V AC</b>
System power	<b>200W</b>
Driver output current / Voltage	<b>48V DC</b>
Ambient temperature	<b>-20 ÷ +45 °C</b>
Weight	<b>0,25 kg</b>

**Description / Descriere / Descrizione**

EN - LED driver 220-240V AC / 48V DC, partially inserted in the recessed or surface profiles of the XFIVE system, magnetic fastening system.

RO - Alimentator 220-240V AC / 48V DC, parțial încadrat în profilele sistemului XFIVE, cu sistem magnetic de fixare, echipat cu un șurub de fixare de siguranță.

IT - Alimentatore LED 220-240V AC / 48V DC, semi incassato nei profili del sistema XFIVE con sistema magnetico di fissaggio.

**Standards**

EN 61347-1:2015 + A1:2021, EN 61347-2-13:2014 + A1:2017, EN 55015:2019 + A11:2020, EN 61000-3-2:2019, EN 61000-3-3:2013 + A1:2019, EN 61547:2023, EN 62717:2017+A2:2019, EN 62722-2-1:2023.

