

# Specificații



Imaginile sunt doar cu titlu informativ



## Eaton LUM17122-L

CrystalWay 20m Viewing Distance CGLine+LUMINOX

### General specifications

<b>PRODUCT NAME</b>	Eaton CrystalWay emergency luminaire
<b>CATALOG NUMBER</b>	LUM17122-L
<b>EAN</b>	3660191807856
<b>PRODUCT LENGTH/DEPTH</b>	231 mm
<b>PRODUCT HEIGHT</b>	31 mm
<b>PRODUCT WIDTH</b>	133 mm
<b>PRODUCT WEIGHT</b>	0.43 kg
<b>CERTIFICATIONS</b>	CE

**EATON**

Powering Business Worldwide

## Specificații produs

<b>BATTERY VOLTAGE</b>	3.6 V
<b>BATTERY QUALITY</b>	Lithium-ions
<b>PERMISSIBLE AMBIENT TEMPERATURE - MIN</b>	5 °C
<b>PERMISSIBLE AMBIENT TEMPERATURE - MAX</b>	35 °C
<b>PROTECTION CLASS</b>	II
<b>DEGREE OF IMPACT RESISTANCE (IK)</b>	IK 04
<b>OUTDOOR USE COMPLIANCE</b>	False
<b>EXPLOSION PROTECTED</b>	False
<b>MODE</b>	Maintained / Non-Maintained (M / NM)
<b>LAMP TYPE</b>	LED not exchangeable
<b>WITH LIGHT SOURCE</b>	True
<b>LAMP HOLDER</b>	Other
<b>LAMP POWER</b>	0.87 W
<b>TYPE OF INDICATOR</b>	Only single-sided
<b>MONITORING EQUIPMENT</b>	Test button
<b>POWER SUPPLY SYSTEM</b>	Peripheral (individual battery)
<b>CIRCUIT</b>	Other
<b>VOLTAGE TYPE</b>	AC
<b>NOMINAL CURRENT - MAX</b>	11 mA
<b>NOMINAL CURRENT - MIN</b>	3 mA
<b>WIRING SYSTEM</b>	Continuous circuit/emergency circuit
<b>WITH REMOTE SWITCH CONNECTION</b>	True
<b>NOMINAL VOLTAGE AC - MAX</b>	230 V
<b>NOMINAL VOLTAGE AC - MIN</b>	230 V
<b>NOMINAL OPERATION TIME - MIN</b>	1 hour
<b>NOMINAL OPERATION TIME - MAX</b>	8 hour
<b>AUTONOMY</b>	1/3/8 hours
<b>MOUNTING METHOD</b>	Surface mounting/recessed mounting
<b>MATERIAL HOUSING</b>	Plastic
<b>COLOR HOUSING</b>	White
<b>MATERIAL COVER</b>	Plastic, transparent
<b>LABELLING TYPE</b>	Insert sheet/plate
<b>PICTOGRAM INCLUDED</b>	True
<b>BUILT-IN LENGTH</b>	212 mm
<b>BUILT-IN WIDTH</b>	57 mm

## Resurse

<b>BUILT-IN HEIGHT/DEPTH</b>	100 mm
<b>KIND OF LUMINAIRE</b>	Exit sign luminaire
<b>LUMINOUS FLUX AT EMERGENCY OPERATION</b>	60 lm
<b>COLOR TEMPERATURE - MAX</b>	6500 K
<b>COLOR TEMPERATURE - MIN</b>	6500 K
<b>COLOR OF LIGHT</b>	White
<b>COLOR RENDERING INDEX (CRI)</b>	80-89
<b>EFFECTIVE LUMINOUS FLUX</b>	6
<b>VIEWING DISTANCE</b>	20 m
<b>FREQUENCY</b>	50/60 Hz
<b>MAIN CONNECTION TERMINAL</b>	0.5 - 2.5mm <sup>2</sup>
<b>TESTING SYSTEM</b>	CGLine +

---

**PROJECT NAME:**

---

**PROJECT NUMBER:**

---

**PREPARED BY:**

---

**DATA:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Irlanda  
Eaton.com

© 2025 Eaton. Toate drepturile rezervate

Eaton este o marcă comercială înregistrată.

Toate celelalte mărci comerciale aparțin proprietarilor lor de drept.

Follow us on social media to get the latest product and support information.

