

Voyager Blade

THORN

96642781 <VOYAGER BLADE EXIT E3M MCH

LED 5W LED_VOYB_60	IEC EN 60598-1 RG 0	IP 30	IK 03		CE	T _a 0 +35
--------------------	---------------------------	-------	-------	---	----	-------------------------

Voyager Blade

Ultra slim, LED exit sign with Local battery luminaire, manual test (3 hours). For suspension mounting. Body: aluminium. Blade: thin plastic. Class I electrical, IP30. Suitable for small area use with viewing distances up to 23 m. Supplied with ISO LEFT/RIGHT legends only.

Dimensions: 268 x 42 x 192 mm

Luminaire input power: 6.1 W

Total luminous flux: 60 lm

Weight: 1.15 kg



TLG_VOYB_F_MSU.jpg

Lamp position: STD - standard
Light Source: LED
Luminaire luminous flux*: 60 lm
Luminaire efficacy*: 10 lm/W
Colour Rendering Index min.: 80

Correlated colour temperature*: 4000 Kelvin
Rated median useful life*:
L50 50000 h at 25 °C
Luminaire input power*: 6.1 W
Maintenance category CIE 97: D - Enclosed IP2X

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Risk group

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting