

QT-FIT8 2X58

QUICKTRONIC FIT 8 | ECG for FL 26 mm



Product family features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 50 Hz | 60 Hz
- Lamp start with optimum filament preheating
- Energy Efficiency Index EEI: A2
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Lamp operation: to EN 60929
- Safety: to EN 61347-2-3

Product family benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Automatic restart after lamp replacement
- Perfect lamp start for applications with motion sensors
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

Areas of application

- Open-plan offices, corridors and storage rooms
- Public buildings
- Strip lighting
- Suitable for emergency lighting (DC operation)
- Suitable for luminaires of protection class I

Product datasheet

Technical data

Electrical data

Input voltage AC	198...264 V
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Input voltage DC	185...264 V ¹⁾
Maximum output power	2 x 58 W
Efficiency in full-load	92 % ²⁾
Operating frequency	40...50 kHz
Max. ECG no. on circuit breaker 10 A (B)	8 ³⁾
Max. ECG no. on circuit breaker 16 A (B)	13 ³⁾
Inrush current	15 A

¹⁾ Minimum voltage for lamp ignition: 198 V, 185...198 V for maximum 1 h


²⁾ at 230 V, 50 Hz

³⁾ Type B

Light technical data

Starting time	2.0 s
---------------	-------

Dimensions & weight



Length	360.0 mm
Width	30.0 mm
Height	28.0 mm
Mounting hole spacing, length	350.0 mm
Product weight	264.00 g
Cable cross-section, output side	0.5...1.5 mm ² ¹⁾
Cable cross-section, input side	0.5...1.5 mm ² ¹⁾

¹⁾ Solid leads

Temperatures & operating conditions

Ambient temperature range	-15...+50 °C
Permitted rel. humidity during operation	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	50000 h ¹⁾
--------------	-----------------------

¹⁾ At maximum T_c / 10% failure rate

Additional product data

Suitable for lamp power (2 lamps)	58 W
-----------------------------------	------

Capabilities

Suitable for fixtures with prot. class	I
End of lamp life safety shutdown	EOL T.2
Max. cable length to lamp/LED module	2.0 m / 1.0 m
Dimmable	No
Intended for no-load operation	No


Certificates & standards

Approval marks – approval	VDE / VDE-EMC / ENEC 10 / CE
EEI – Energy Label	A2
Standards	Acc. to EN 61347-2-3/Acc. to EN 60929/Acc. to EN 55015:2006 + A1:2007/Acc. to EN 61000-3-2/Acc. to EN 61547
Protection class	I
Type of protection	IP20

Logistical data


Commodity code	850410809000
----------------	--------------

Wiring Diagram



QUICKTRONIC® FIT T5/T8

Series	QT-FIT8 3x36W	QT-FIT8 1x36W	QT-FIT8 2x36W	QT-FIT8 3x36W
Max. W	17 A	17 A	16 A	8 A
Max. IEC	8 700 VA @ 230 V	8 700 VA @ 230 V	8 700 VA @ 230 V	8 700 VA @ 230 V
Max. IEC	20 47 A	20 47 A	19 32 A	13 22 A
Max. IEC	8 700 VA @ 230 V	8 700 VA @ 230 V	8 700 VA @ 230 V	8 700 VA @ 230 V
Ta	420 A	420 A	440 A	450 A
Ta	200 µs	200 µs	200 µs	200 µs



319608_QT FIT8 2x..

590720_EAC QT-FIT8

Download Data

File
Product Datasheet 321439_ATI QT-FIT8 2x58 (G+GB)
Certificates 334974_ENEC-Marks approval
Certificates 335097_INOTEC
Certificates 335150_CEAG
Certificates 335169_Manufacturer's declaration & #150; LampECG combinations: Frequent switching
Certificates 592319_EAC certificate for Quicktronics QT
Certificates 504209_VDE-EMC-Certificate QT-Fit8
Declarations of conformity Quicktronic CE 3364256 090421
CAD data 3-dim 316108_QUICKTRONIC QT-FIT8 360x30x28 9900051

Product datasheet



CAD data 3-dim
316109_QUICKTRONIC QT-FIT8 360x30x28 9900051



CAD data 3-dim
316110_QUICKTRONIC QT-FIT8 360x30x28 9900051



CAD data PDF
316101_QUICKTRONIC QT-FIT8 360x30x28 9900051

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321294289	QT-FIT8 2X58	Shipping carton box 20	391 mm x 131 mm x 161 mm	8.25 dm ³	5941.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

QT-FIT8 2X58

QUICKTRONIC FIT 8 | ECG for FL 26 mm

Product name	Lamp group
QT-FIT8 2X58	L 58 W