



Main

| | |
|---------------------------|------------------|
| Range of product | Acti 9 |
| Product name | Acti 9 iTR |
| Product or component type | Transformer |
| Device short name | ITR |
| Transformer type | Bell transformer |

Complementary

| | |
|---------------------------------|---|
| [Ue] rated operational voltage | 230 V AC 50/60 Hz |
| Output voltage | 12/24 V : +/- 15 % on load 16/32 V : off load |
| Output short-circuit protection | Built-in |
| Rated power in VA | 25 VA |
| Mounting mode | Fixed |
| Mounting support | 35 mm symmetrical DIN rail |
| 9 mm pitches | 6 |
| Height | 89 mm |
| Width | 54 mm |
| Depth | 60 mm |
| Colour | White |
| Auxiliary connection terminal | Tunnel type terminals rigid <= 2.5 mm ² Tunnel type terminals flexible <= 2.5 mm ² Tunnel type terminals flexible with ferrule <= 2.5 mm ² |
| Wire stripping length | 6 mm |
| Tightening torque | 0.5 N.m |

Environment

| | |
|-------------------------|---|
| Standards | EN 60742 EN 61558-2-6 IEC 61558-2-6 |
| Product certifications | NF |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Overvoltage category | Class II with terminal shields in option |

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -20...55 °C |
| Ambient air temperature for storage | -25...80 °C |

Offer Sustainability

| | |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1312 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
