


Flush-mounting auxiliary touch module with one command.

Two touch areas on the front, this product can be used in combination with the auxiliary wired inputs of the following devices of the Chorusmart range: connected commands, connected 1- channel On/Off actuator, connected movement sensors, TOUCH and EVO commands, or as a wired command for a connected 2-channel ZigBee interface.

The device must be completed with one of the ICE Touch plates available. Inside the package of the plates is a sheet of interchangeable icons to customize the control symbol.

Descriere	Auxiliary touch 1-command module	Sursă de alimentare	100 + 240 V ac - 50/60 Hz
Nr. module	1	Nr. canale în intrare	-
Local control	Via 2 frontal touch areas (must be completed with ICE Touch plate)	Auxiliary input channel voltage	-
Temperatură de stocare	-25 + +70 °C	Nr. canale în ieșire	1
Temperatură de funcționare	-5 +45 °C	Contacte de ieșire	-
Relative humidity (non-condensative)	Max 93%	240 V ac Incandescent-halogen lamps	-
Front light signaling	Led albastru	240 V ac LED lamps	-
Terminale de cablare	Cu șuruburi	Loads piloted from electronic transf. 240 V ac	-
Capacitate strângere terminal cabluri flexibile (mm ²)	Max. 1,5	240 V Fluorescent lamps	-
Capacitate strângere terminal cabluri rigide (mm ²)	Max. 1,5	Load control	-
Context	Dry indoor places	Acoustic signalling element	Buzzer
Clasă de protecție IP	IP20 (with plate fitted)	Standard	2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN IEC 63000

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with plate fitted)

STANDARDS/APPROVALS

