

# Product data sheet

Specifications



## Asfora - double 1pole pushbutton - 10A screwless terminals, white

EPH1100121

### Main

|                           |                  |
|---------------------------|------------------|
| Range                     | Asfora           |
| Product or component type | Push-button      |
| Device presentation       | Complete product |
| Colour tint               | White<br>White   |
| Type of packing           | Flow-pack        |

### Complementary

|                         |                                       |
|-------------------------|---------------------------------------|
| Device mounting         | Flush                                 |
| Number of rocker        | 2                                     |
| Power range             | 2300 W                                |
| Rated current           | 10 A at 250 V AC                      |
| Connections - terminals | Screwless terminals                   |
| Number of cables        | 2 cable(s) 2.5 mm <sup>2</sup>        |
| Cable stiffness         | Flexible<br>Rigid<br>Solid stranded   |
| Wire stripping length   | 13.0 mm                               |
| Material                | ABS (acrylonitrile butadiene-styrene) |
| Surface finish          | Glossy                                |
| Conductor material      | Copper                                |
| Fixing mode             | Screws or claws51...70 mm             |
| Height                  | 83 mm                                 |
| Width                   | 83 mm                                 |
| Depth                   | 43.0 mm                               |
| Projecting depth        | 15 mm                                 |
| Net weight              | 0.0732 kg                             |

### Environment

|                        |             |
|------------------------|-------------|
| Standards              | IEC 60669-1 |
| Product certifications | TSE         |

VDE  
NF

Quality labels CE  
UKR

IP degree of protection IP20

Ambient air temperature for operation -5...40 °C

## Packing Units

Unit Type of Package 1 Db

Number of Units in Package 1 1

Package 1 Height 4.000 cm

Package 1 Width 8.500 cm

Package 1 Length 8.500 cm

Package 1 Weight 75.000 g

Unit Type of Package 2 Gyári csomagolás

Number of Units in Package 2 10

Package 2 Height 9.300 cm

Package 2 Width 18.500 cm

Package 2 Length 27.500 cm

Package 2 Weight 802.000 g

Unit Type of Package 3 S04

Number of Units in Package 3 120

Package 3 Height 30.000 cm

Package 3 Width 40.000 cm

Package 3 Length 60.000 cm

Package 3 Weight 10.154 kg

## Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Compliant  
[EU RoHS Declaration](#)

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

RoHS exemption information Yes

Environmental Disclosure [Product Environmental Profile](#)

WEEE The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty 18 months

## Recommended replacement(s)