



### Principal

Gama	TeSys
Nume produs	TeSys D
Tip produs sau componenta	Contactor
Nume scurt al dispozitivului	LC1D
Aplicatie contactor	Sarcina rezistiva Comanda motor
Categorie de utilizare	AC-3 AC-1 AC-4
Descriere poli	3P
Power pole contact composition	3 NO
[Ue] tensiune nominala de functionare	Power circuit: $\leq 690$ V AC 25...400 Hz Power circuit: $\leq 300$ V DC
[Ie] curent nominal de utilizare	32 A (at $\leq 60$ °C) at $\leq 440$ V AC AC-3 for power circuit 50 A (at $\leq 60$ °C) at $\leq 440$ V AC AC-1 for power circuit
Putere motor kW	7.5 kW at 220...230 V AC 50/60 Hz (AC-3) 15 kW at 380...400 V AC 50/60 Hz (AC-3) 15 kW at 415...440 V AC 50/60 Hz (AC-3) 18.5 kW at 500 V AC 50/60 Hz (AC-3) 18.5 kW at 660...690 V AC 50/60 Hz (AC-3) 7.5 kW at 400 V AC 50/60 Hz (AC-4)
Motor power HP (UL / CSA)	2 hp at 115 V AC 50/60 Hz for 1 phase motors 5 hp at 230/240 V AC 50/60 Hz for 1 phase motors 7.5 hp at 200/208 V AC 50/60 Hz for 3 phases motors 10 hp at 230/240 V AC 50/60 Hz for 3 phases motors 20 hp at 460/480 V AC 50/60 Hz for 3 phases motors 30 hp at 575/600 V AC 50/60 Hz for 3 phases motors
Tipul circuitului de comanda	DC standard
[Uc] tensiune circuit de comanda	24 V DC
Compozitie contact auxiliar	1 NO + 1 NC
[Uimp] tensiune de tinere la impuls	6 kV conforming to IEC 60947

Declinare de responsabilitate: Această documentație nu se substituie și nu trebuie utilizată pentru stabilirea adecvării sau fiabilității acestor produse pentru aplicații utilizator

Categorie de supratensiune	III
[Ith] curent termic conventional in aer liber	10 A (at 60 °C) for signalling circuit 50 A (at 60 °C) for power circuit
Irms capacitatea nominala la inchidere	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 550 A at 440 V for power circuit conforming to IEC 60947
Capacitate de rupere nominala	550 A at 440 V for power circuit conforming to IEC 60947
[Icw] curent nominal de scurtcircuit admisibil	260 A 40 °C - 10 s for power circuit 430 A 40 °C - 1 s for power circuit 60 A 40 °C - 10 min for power circuit 138 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Calibrul fuzibilului asociat	10 A gG for signalling circuit conforming to IEC 60947-5-1 63 A gG at <= 690 V coordination type 1 for power circuit 63 A gG at <= 690 V coordination type 2 for power circuit
Impedanta medie	2 mOhm - Ith 50 A 50 Hz for power circuit
[Ui] tensiune nominala de izolatie	Power circuit: 690 V conforming to IEC 60947-4-1 Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified
Durabilitate electrica	1.65 Mcycles 32 A AC-3 at Ue <= 440 V 1.4 Mcycles 50 A AC-1 at Ue <= 440 V
Puterea disipata pe pol	2 W AC-3 5 W AC-1
Front cover	Cu
Suport de montare	Sina Placa
Standarde	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Certificari produs	DNV GL CCC UL GOST BV LROS (Lloyds register of shipping) RINA CSA UKCA
Conexiuni - borne	Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> solid without cable end Power circuit: screw clamp terminals 1 cable(s) 2.5...10 mm <sup>2</sup> flexible without cable end Power circuit: screw clamp terminals 2 cable(s) 2.5...10 mm <sup>2</sup> flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 1...10 mm <sup>2</sup> flexible with cable end Power circuit: screw clamp terminals 2 cable(s) 1.5...6 mm <sup>2</sup> flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 1.5...10 mm <sup>2</sup> solid without cable end Power circuit: screw clamp terminals 2 cable(s) 2.5...10 mm <sup>2</sup> solid without cable end
Cuplu de strangere	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver Philips No 2
Timp de functionare	53.55...72.45 ms closing 16...24 ms opening
Nivel de incredere al securitatii	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Durabilitate mecanica	30 Mcycles

Viteza maxima de functionare	3600 cyc/h 60 °C
------------------------------	------------------

## Suplimentar

Tehnologie bobine	Supresor cu dioda limitatoare de varf bidirectionalaincorporat
Limite de tensiune circuit de comanda	0.1...0.25 Uc (-40...70 °C):drop-out DC 0.7...1.25 Uc (-40...60 °C):operational DC 1...1.25 Uc (60...70 °C):operational DC
Constanta de timp	28 ms
Vârf de putere în W	5.4 W (at 20 °C)
Consum de energie mentinere in W	5.4 W at 20 °C
Tip contacte auxiliare	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Afisare frecventa circuit	25...400 Hz
Curentul minim de comutare	5 mA for signalling circuit
Tensiunea minima de comutare	17 V for signalling circuit
Timpul de nesuprapunere	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Rezistenta de izolatie	> 10 MOhm for signalling circuit

## Mediu

Grad de protectie IP	IP20 front face conforming to IEC 60529
Tratament protector	TH conforming to IEC 60068-2-30
Grad de poluare	3
Temperatura ambientala de utilizare	-40...60 °C 60...70 °C with derating
Temperatura de depozitare	-60...80 °C
Altitudinea de functionare	0...3000 m
Rezistenta la foc	850 °C conformitate cu IEC 60695-2-1
Intarziere flacara	V1 conforming to UL 94
Rezistenta mecanica	Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 4 Gn, 5...300 Hz Shocks contactor closed: 15 Gn for 11 ms Shocks contactor open: 8 Gn for 11 ms
Inaltime	85 mm
Latime	45 mm
Adancime	101 mm
Greutate neta	0,535 kg

## Packing Units

Tip unitate a formei de impachetare 1	PCE
Număr de produse în pachet	1
Greutate colet(Lbs)	588 g
Inaltimea formei de impachetare 1	5 cm
Latimea formei de impachetare 1	9 cm
Lungimea formei de impachetare 1	11 cm
Tip unitate a formei de impachetare 2	S02
Numar de unitati in forma de impachetare 2	15
Greutatea formei de impachetare 2	9,275 kg
Inaltimea formei de impachetare 2	15 cm
Latimea formei de impachetare 2	30 cm
Lungimea formei de impachetare 2	40 cm
Tip unitate a formei de impachetare 3	P06
Numar de unitati in forma de impachetare 3	240

Greutatea formei de impachetare 3	155,22 kg
Inaltimea formei de impachetare 3	80 cm
Latimea formei de impachetare 3	80 cm
Lungimea formei de impachetare 3	60 cm

### Offer Sustainability

Stare ofertă sustenabilă	Produs Green Premium
Regulamentul REACH	<a href="#">Declaratia REACH</a>
Conform REACH fara SVHC	Da
Directiva RoHS UE	Conform <a href="#">Declaratia RoHS UE</a>
Fara metale grele toxice	Da
Fara mercur	Da
Informatii privind scutirea de la RoHS	<a href="#">Da</a>
Regulamentul RoHS China	<a href="#">Declaratia RoHS China</a> Declaratia proactiva RoHS China (in afara domeniului de aplicare a RoHS China)
Raport de mediu	<a href="#">Profilul ambiental al produsului</a>
Profil circularitate	<a href="#">Informatii privind sfarsitul duratei de viata</a>
WEEE	În Uniunea Europeana, produsele trebuie reciclate respectand sistemul specific de colectare a deseurilor si nu trebuie sa ajunga in pubelele de colectare a deseurilor menajere.
Fara PVC	Da

### Garanție contractuală

Garantie	18 luni
----------	---------