



Principal

Gama	TeSys
Nume produs	TeSys D
Tip produs sau componenta	Contactor
Nume scurt al dispozitivului	LC1D
Aplicatie contactor	Comanda motor Sarcina rezistiva
Categorie de utilizare	AC-4 AC-1 AC-3
Descriere poli	3P
Power pole contact composition	3 NO
[Ue] tensiune nominala de functionare	Power circuit: ≤ 300 V DC 25...400 Hz Power circuit: ≤ 690 V AC
[Ie] curent nominal de utilizare	125 A (at ≤ 60 °C) at ≤ 440 V AC AC-1 for power circuit 80 A (at ≤ 60 °C) at ≤ 440 V AC AC-3 for power circuit
Putere motor kW	22 kW la 220...230 V c.a. 50/60 Hz (AC-3) 37 kW la 380...400 V c.a. 50/60 Hz (AC-3) 45 kW la 415...440 V c.a. 50/60 Hz (AC-3) 55 kW la 500 V c.a. 50/60 Hz (AC-3) 45 kW la 660...690 V c.a. 50/60 Hz (AC-3) 45 kW la 1000 V c.a. 50/60 Hz (AC-3) 15 kW la 400 V c.a. 50/60 Hz (AC-4)
Motor power HP (UL / CSA)	20 hp at 200/208 V AC 50/60 Hz for 3 phases motors 7.5 hp at 115 V AC 50/60 Hz for 1 phase motors 15 hp at 230/240 V AC 50/60 Hz for 1 phase motors 25 hp at 230/240 V AC 50/60 Hz for 3 phases motors 60 hp at 460/480 V AC 50/60 Hz for 3 phases motors 60 hp at 575/600 V AC 50/60 Hz for 3 phases motors
Tipul circuitului de comanda	AC at 50/60 Hz
[Uc] tensiune circuit de comanda	110 V c.a. 50/60 Hz
Compozitie contact auxiliar	1 NO + 1 NC

Declinare de responsabilitate: Această documentație nu se substituie și nu trebuie utilizată pentru stabilirea adecvării sau fiabilității acestor produse pentru aplicații utilizator

[Uimp] tensiune de tinere la impuls	8 kV conforming to IEC 60947
Categorie de supratensiune	III
[Ith] curent termic conventional in aer liber	10 A (at 60 °C) for signalling circuit 125 A (at 60 °C) for power circuit
Irms capacitatea nominala la inchidere	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 1100 A at 440 V for power circuit conforming to IEC 60947
Capacitate de rupere nominala	1100 A at 440 V for power circuit conforming to IEC 60947
[Icw] curent nominal de scurtcircuit admisibil	640 A 40 °C - 10 s for power circuit 990 A 40 °C - 1 s for power circuit 135 A 40 °C - 10 min for power circuit 320 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Calibrul fuzibilului asociat	10 A gG for signalling circuit conforming to IEC 60947-5-1 200 A gG at <= 690 V coordination type 1 for power circuit 160 A gG at <= 690 V coordination type 2 for power circuit
Impedanta medie	0.8 mOhm - Ith 125 A 50 Hz for power circuit
[Ui] tensiune nominala de izolatie	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified
Durabilitate electrica	0.8 Mcycles 125 A AC-1 at Ue <= 440 V 1.5 Mcycles 80 A AC-3 at Ue <= 440 V
Puterea disipata pe pol	5.1 W AC-3 12.5 W AC-1
Front cover	Cu
Suport de montare	Sina Placa
Standarde	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Certificari produs	GL RINA BV DNV LROS (Lloyds register of shipping) CCC GOST UL CSA UKCA
Conexiuni - borne	Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm ² flexible without cable end Circuit de comanda borne cu surub 1 cablu(ri) 1...4 mm ² solid fara Circuit de comanda borne cu surub 2 cablu(ri) 1...4 mm ² solid fara Power circuit: connector 1 cable(s) 4...50 mm ² flexible without cable end Power circuit: connector 2 cable(s) 4...25 mm ² flexible without cable end Power circuit: connector 1 cable(s) 4...50 mm ² flexible with cable end Power circuit: connector 2 cable(s) 4...16 mm ² flexible with cable end Circuit electric conector 1 cablu(ri) 4...50 mm ² solid fara Circuit electric conector 2 cablu(ri) 4...25 mm ² solid fara
Cuplu de strangere	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm
Timp de functionare	20...35 ms închidere 6...20 ms deschidere
Nivel de incredere al securitatii	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1

Durabilitate mecanica	4 Mcycles
Viteza maxima de functionare	3600 cyc/h 60 °C

Suplimentar

Tehnologie bobine	Fără modul de deparazitare inclus
Limite de tensiune circuit de comanda	0,85...1,1 Uc -40...55 °C operațional c.a. 60 Hz 0,3...0,6 Uc (-40...70 °C):drop-out AC 50/60 Hz 0,8...1,1 Uc -40...55 °C operațional c.a. 50 Hz 1...1,1 Uc 55...70 °C operațional c.a. 50/60 Hz
Consum de energie conectare in VA	245 VA 60 Hz 0,75 20 °C) 245 VA 50 Hz 0,75 20 °C)
Consum de energie mentinere in VA	26 VA 60 Hz 0,3 20 °C) 26 VA 50 Hz 0,3 20 °C)
Disipare de caldura	6...10 W la 50/60 Hz
Tip contacte auxiliare	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Afisare frecventa circuit	25...400 Hz
Curentul minim de comutare	5 mA for signalling circuit
Tensiunea minima de comutare	17 V for signalling circuit
Timpul de nesuprapunere	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Rezistenta de izolatie	> 10 MOhm for signalling circuit

Mediu

Grad de protectie IP	IP20 front face conforming to IEC 60529
Tratament protector	TH conforming to IEC 60068-2-30
Grad de poluare	3
Temperatura ambientala de utilizare	-40...60 °C 60...70 °C with derating
Temperatura de depozitare	-60...80 °C
Altitudinea de functionare	0...3000 m
Rezistenta la foc	850 °C conformitate cu IEC 60695-2-1
Intarziere flacara	V1 conforming to UL 94
Rezistenta mecanica	Vibrations contactor open: 2 Gn, 5...300 Hz Shocks contactor open: 8 Gn for 11 ms Vibrations contactor closed: 3 Gn, 5...300 Hz Shocks contactor closed: 10 Gn for 11 ms
Inaltime	127 mm
Latime	85 mm
Adancime	130 mm
Greutate produs	1,59 kg

Packing Units

Tip unitate a formei de impachetare 1	PCE
Număr de produse în pachet	1
Greutate colet(Lbs)	1,558 kg
Inaltimea formei de impachetare 1	9,4 cm
Latimea formei de impachetare 1	13,4 cm
Lungimea formei de impachetare 1	14,2 cm

Offer Sustainability

Stare ofertă sustenabilă	Produs Green Premium
Regulamentul REACH	Declaratia REACH
Conform REACH fara SVHC	Da
Directiva RoHS UE	Conform

Declaratia RoHS UE

Fara metale grele toxice	Da
Fara mercur	Da
Informatii privind scutirea de la RoHS	Da
Regulamentul RoHS China	Declaratia RoHS China Declaratia proactiva RoHS China (in afara domeniului de aplicare a RoHS China)
Raport de mediu	Profilul ambiental al produsului
WEEE	În Uniunea Europeana, produsele trebuie reciclate respectand sistemul specific de colectare a deseurilor si nu trebuie sa ajunga in pubelele de colectare a deseurilor menajere.
Fara PVC	Da

Contractual warranty

Garantie	18 months
----------	-----------