

Specificații

Eaton 265181

Z-R230/SO. Installation relay, 230VAC/50Hz, 1N/O+1N/C, 20A, 1HP

General specifications

PRODUCT NAME	Eaton Distribution parts
CATALOG NUMBER	265181
EAN	4015082651817
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	70 mm
PRODUCT WIDTH	17.5 mm
PRODUCT WEIGHT	0.136 kg
COMPLIANCES	RoHS conform CE Marked
MODEL CODE	Z-R230/SO



Specificații produs

AMPERAGE RATING	20 A
MOUNTING METHOD	DIN rail
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	6.4 W
CONTROL VOLTAGE 1 TYPE	AC
AMBIENT OPERATING TEMPERATURE - MAX	45 °C
AMBIENT OPERATING TEMPERATURE - MIN	-20 °C
CONTROL VOLTAGE 1 - MAX	230 V
CONTROL VOLTAGE 1 - MIN	230 V
CONTROL VOLTAGE 2 - MAX	0 V
CONTROL VOLTAGE 2 -	0 V

Resurse

DECLARATIONS OF CONFORMITY [DA-DC-03 Z-R](#)

MIN	
FREQUENCY CONTROL VOLTAGE 1 - MAX	50 Hz
FREQUENCY CONTROL VOLTAGE 1 - MIN	50 Hz
FREQUENCY CONTROL VOLTAGE 2 - MAX	0 Hz
FREQUENCY CONTROL VOLTAGE 2 - MIN	0 Hz
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	2 W
INCANDESCENT LAMP LOAD - MAX	0 W
LOAD FLUORESCENT LAMP - MAX	0 VA
LOAD FLUORESCENT LAMP (DUO CIRCUIT) - MAX	0 VA
LOAD FLUORESCENT LAMP (PARALLEL COMPENSATED) - MAX	0 VA
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
CONTROL VOLTAGE 2 TYPE	AC/DC
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	20 A
SUPPLY VOLTAGE - MAX	250 V
SUPPLY VOLTAGE - MIN	250 V
SWITCHING CURRENT (COS PHI = 0.6) - MAX	0 A
WIDTH IN NUMBER OF MODULAR SPACINGS	1
BUILT-IN DEPTH	60 mm
VOLTAGE TYPE	AC
FUNCTIONS	Mechanical

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Irlanda
Eaton.com

© 2025 Eaton. Toate
drepturile rezervate

Eaton este o marcă comercială
înregistrată.

Toate celelalte mărci comerciale
aparțin proprietarilor lor de
drept.

Follow us on social media to get the latest
product and support information.

