

Product data sheet

Specifications



Short terminal shield, ComPacT NSX400/630, pitch 45mm, IP40, 4 poles

LV432592

Main

Product or component type	Short terminal shield
Range compatibility	ComPacT new generation (ComPacT NSX400 new generation) ComPacT new generation (ComPacT NSX630 new generation) ComPact (ComPact NSX400) ComPact (ComPact NSX630) ComPacT new generation (ComPacT NSX DC new generation) NSX400 DC ComPacT new generation (ComPacT NSX DC new generation) NSX630 DC ComPact Compact NSX400 DC ComPact Compact NSX630 DC EasyPact (EasyPact CVS400) EasyPact (EasyPact CVS630) ComPact (Compact INV) ComPact (ComPacT INS)
Accessory / separate part type	Insulation accessories
Poles description	4P
Quantity per set	1

Complementary

Connection pitch	45 mm
IP degree of protection	IP40 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.6 cm
Package 1 Width	12.5 cm
Package 1 Length	27.4 cm
Package 1 Weight	147.0 g
Unit Type of Package 2	P12
Number of Units in Package 2	120
Package 2 Height	45.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	33.168 kg
Unit Type of Package 3	S03

Number of Units in Package 3	15
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	2.646 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
-----------------	-----------