

# Product datasheet

Specifications



## Linergy DS - screw distribution block 1P - 250A - 14 holes

LGY125014

### Main

Range	Linergy
Product Name	Linergy DS
Product Or Component Type	Distribution block

### Complementary

Mounting Support	DIN rail
Range Compatibility	Prisma G Prisma P Prisma PH Spacial TeSys
Product Compatibility	Spacial enclosures
Poles Description	1P
Distribution Block Outgoers	14 holes
[Ue] Rated Operational Voltage	230 V AC Ph/N 440 V AC Ph/Ph
[Ui] Rated Insulation Voltage	500 V AC
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ie] Rated Operational Current	250 A at 40 °C
[Icw] Rated Short-Time Withstand Current	14.4 kA for 1 s
[Ipk] Rated Peak Withstand Current	60 kA
Connections - Terminals	Distribution: screw terminal 4 cable(s) 1.5...16 mm <sup>2</sup> rigid Distribution: screw terminal 4 cable(s) 1.5...10 mm <sup>2</sup> flexible with cable end Distribution: screw terminal 8 cable(s) 2.5...25 mm <sup>2</sup> rigid Distribution: screw terminal 8 cable(s) 1.5...16 mm <sup>2</sup> flexible with cable end Supply: screw terminal 1 cable(s) 35...120 mm <sup>2</sup> rigid Supply: screw terminal 1 cable(s) 23...95 mm <sup>2</sup> flexible with cable end Distribution: screw terminal 1 cable(s) 1.5...50 mm <sup>2</sup> rigid Distribution: screw terminal 1 cable(s) 1.5...35 mm <sup>2</sup> flexible with cable end
Tightening Torque	Distribution: 2 N.m flat screwdriver 7.5 mm Distribution: 2 N.m PZ2 screwdriver 7.5 mm Supply: 10 N.m flat screwdriver 15.3 mm Supply: 10 N.m PZ2 screwdriver 15.3 mm Distribution: 4 N.m flat screwdriver 10 mm Distribution: 4 N.m PZ2 screwdriver 10 mm Distribution: 2 N.m flat screwdriver 6 mm Distribution: 2 N.m PZ2 screwdriver 6 mm
9 Mm Pitches	5
Height	85 mm
Width	45 mm

Depth	50.5 mm
Net Weight	0.252 kg
Colour	White (RAL 9003)

## Environment

Pollution Degree	3
Overvoltage Category	III
Dielectric Strength	2500 V
Standards	EN/IEC 60947-7-1 EN/IEC 61439-1
Ambient Air Temperature For Operation	-25...55 °C

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	5.500 cm
Package 1 Length	9.000 cm
Package 1 Weight	253.000 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	40
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	10.670 kg

## Contractual warranty

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more >](#)

## Well-being performance

✓ Toxic Heavy Metal Free

---

✓ Mercury Free

---

✓ Rohs Exemption Information [Yes](#)

---

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** Compliant  
[EU RoHS Declaration](#)

---

**China Rohs Regulation** [China RoHS declaration](#)  
Pro-active China RoHS declaration (out of China RoHS legal scope)

---

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---