



### Main

Range	Vigilohm
Range of product	Vigilohm
Device short name	HRP
Product or component type	Hospital remote panel
Range compatibility	Vigilohm IM IM20-H
Sound signalling	Insulation or electrical fault: buzzer adjustable 80 dB

### Complementary

Auxiliary supply voltage	24 V DC
Current consumption	65 mA
Material	Plastic
Control type	Push-button: test installation insulation Push-button: stop alarm buzzer
Local signalling	Insulation fault: indicator light (orange) Electrical fault: indicator light (red) Normal operation: indicator light (green)
Product weight	0.5 kg
Width	170 mm
Height	170 mm
Depth	20 mm

### Environment

IP degree of protection	IP54
IK degree of protection	IK08
Operating altitude	2000 m
Relative humidity	90 %
Standards	IEC 60364-7-710: medical location IEC 61557-8: safety IEC 60601-1: medical electrical equipment
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-25...70 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	342 g
Package 1 Height	7.5 cm
Package 1 width	20.5 cm
Package 1 Length	21.5 cm
Unit Type of Package 2	S04
Number of Units in Package 2	10
Package 2 Weight	4.13 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Contractual warranty

Warranty	18 months
----------	-----------